

CAP COLOR


W	WHITE
K	BLACK
R	RED
B	BULE
N	WITHOUT
T	Transparent

SPECIFICATION :


1. RATING : 30VDC/100mA[**MAX**];5VDC/1mA[**MIN**] .
2. CONTACT RESISTANCE : 180 $\Omega$ , MAX .
3. INSULATION RESISTANCE : 100 V DC - 100 M $\Omega$ , MIN .
4. WITHSTAND VOLTAGE : 250 V AC - 1 MINUTE .
5. OPERATING FORCE : 125  $\pm$  50 gf .
6. LIFE CYCLE : 500,000 CYCLE .

DIMENSION	TOLERANCE
BELOW 10 mm	$\pm 0.25$
10~50 mm	$\pm 0.4$
ABOVE 50 mm	$\pm 0.7$


SW CIRCUIT



LED CIRCUIT



P.C.B.LAYOUT



UNIT	mm	MODE	TACT SWITCH WITH LED								
SCALE	1 : 1	ANGLE TER	$\pm 3^\circ$								
VER	DATE	APPROVAL	CONFIRM	DESIGN	ENGINEERING RECORD DESCRIPTION	PART	TL3-N1CBRG-AF2T	VIEW		PHONE	(86)755-29424722/29424733